


ALUMINIUM VENETIAN INSTALLATION GUIDE

INSTALLATION OPERATING AND CARE INSTRUCTIONS



MATERIALS & TOOLS

Each Venetian Blind ordered should include:

- Spring loaded mounting brackets (No. depends on size)
- 2 hold-down brackets
- 2 cord cleats and screws

TOOLS REQUIRED


- Steel measuring tape
- Carpenter's level

- Power or battery drill and bits
- Flat blade and Phillips head screwdrivers
- Scissors
- 2 screws for each bracket (20mm x 6 #Panhead)

25MM ALUMINIUM VENETIANS

MOUNTING THE BRACKET


The installation brackets may be Reveal (inside the window frame) or Face (outside the window frame) mounted. In all cases, level mounting is critical to the operation of the blind (use Carpenter's level).



REVEAL FIT (INSIDE MOUNT)

Hold the Venetian inside window frame and mark position of brackets so as not to foul tape drums. Attach the brackets with screws provided, (1 per bracket for top fix), to the front of the reveal, ensuring the front edges are in line and level. This is the usual position, however you may want to fit them further back into the reveal.


NOTE: May need to use washers or packing to ensure level.



FACE FIT (OUTSIDE MOUNT)


Hold the Venetian on the face of the window and mark position of brackets, so as not to foul tape drums. Attach the brackets with screws provided (2 per bracket for face fit) ensuring all brackets are in line and level.

NOTE: Blind will close tighter if fitted level. If headbox bows poor closure will result.



CONTROL END BRACKET LOCATION


	TILT AND LIFT SAME END	TILT AND LIFT OPPOSITE END
25mm	80mm from end of headrail to centre of bracket.	55mm from end of headrail to centre of bracket.



Intermediate brackets should be spaced evenly and as close to tape drums supports as practical.


FACE FIXING ONTO CEMENT RENDERED WALLS

Do not drill too close to edge as render may break away. Use suitable rawl plugs in conjunction with the screws supplied.




FIXED TO CLEAR HANDLES ETC

If needing to pack out from window to clear handles, locks etc use a full width piece of timber as this is more stable than individual pieces and you are able to fix brackets to timber in any position.




INSTALLING THE BLIND

Simply slip the headrail onto the front hooks of the bracket, push inwards and twist the back of the headrail upwards in one motion. The headrail will snap into position.



HOLD DOWN BRACKETS (OPTIONAL)

Hold-down Brackets are used to keep the bottom of the blind from swaying in the breeze. They may be Reveal (inside the window frame) or Face (outside the window frame) mounted. With the blind fully lowered, place the hold-down brackets onto the pins of the bottom rail and mark the hole locations. Attach the bracket with screw supplied (20mm x 6 #Panhead). Place the bottom rail into the brackets, open and close the blind.




REMOVAL OF BLIND

To remove, open slats and raise the blind. If the blind has three or more brackets, remove the headrail from both ends first, leaving the centre bracket to last. Push the headrail in and twist down at the back of the headrail to release the headbox from the hooks at the back. Leave the headbox hanging on the front hooks. Repeat at each bracket, then lift the blind from the bracket and take down.

WAND TILT CLUTCH (OPTIONAL)

To protect your blind from overwinding, some Aluminium Venetian Blinds come with a clutch in the top of the wand. When too much pressure is applied the teeth of the clutch skip over each other to prevent damage.



PROTECT YOUR CHILDREN

Be aware that it is possible for children to strangle in window covering cords. To reduce the possibility of such an accident, all cords must be kept out of the reach of children, including infants. Cord cleats are an effective way to implement this essential precaution.

Attach the cord cleats 153mm to 305mm apart at a height where they will be out of the reach of children. Take into account that a child may stand on a baby cot or other furniture in an attempt to reach the cords. Once the cleats are attached, simply wrap the excess cord around them after each use of the shade, as shown. It's fast, easy and safe.



OPERATION

WAND TILT: simply rotate the wand to tilt the slats from fully closed to any desired angle.

RAISING & LOWERING OF BLIND: to raise, tilt the slats to the fully opened position. Remove the bottom rail from the hold-down brackets (if fitted). Pull the lift cord towards the centre and raise the blind. To lock in position simply move the cord towards the outer edge of the blind to engage the cord lock. To lower, simply pull the cord towards the centre of the blind and lower gently.


CARE AND CLEANING

1. Dust can be easily brushed off at regular intervals using a clean soft cloth, a feather duster, or a vacuum cleaner with brush attachment.
2. To dust, tilt the slats up and then down (but not entirely closed) to reach the entire top and bottom surfaces.
3. To vacuum, use the brush attachment and tilt slats as per 2. above.
4. Slats may be wiped over with warm water and a mild detergent.


50MM ALUMINIUM VENETIAN BLINDS

MOUNTING THE BRACKET

The installation brackets may be Reveal (inside the window frame) or Face (outside the window frame) mounted. In all cases, level mounting is critical to the operation of the blind (use Carpenter's level).



REVEAL FIT BRACKET




FACE FIT BRACKET

REVEAL FIT (INSIDE MOUNT)

Hold the Venetian inside window frame and mark position of brackets so as not to foul tape drums. Attach the brackets with screws provided, (1 per bracket for top fix), to the front of the reveal, ensuring the front edges are in line and level. This is the usual position, however you may want to fit them further back into the reveal.


NOTE: May need to use washers or packing to ensure level.



FACE FIT (OUTSIDE MOUNT)


Hold the Venetian on the face of the window and mark position of brackets, so as not to foul tape drums. Attach the brackets with screws provided (2 per bracket for face fit) ensuring all brackets are in line and level.

NOTE: Blind will close tighter if fitted level. If headbox bows poor closure will result.




FACE FIXING ONTO CEMENT RENDERED WALLS

Do not drill too close to edge as render may break away. Use suitable rawl plugs in conjunction with the screws supplied.




FIXED TO CLEAR HANDLES ETC

If needing to pack out from window to clear handles, locks etc use a full width piece of timber as this is more stable than individual pieces and you are able to fix brackets to timber in any position.




INSTALLING THE BLIND

Simply slip the headrail onto the front hooks of the bracket, push inwards and twist the back of the headrail upwards in one motion. The headrail will snap into position.



HOLD DOWN BRACKETS (OPTIONAL)

Hold-down Brackets are used to keep the bottom of the blind from swaying when mounted on doors or exposed to the wind. The hold-down brackets are inside or outside mounted at the bottom of the window opening. With the blind fully lowered, place the hold-down brackets on to the pins on the end of the bottom rail and mark mounting hole locations. Attach hold-down brackets with screws provided. With the bottom rail attached to the hold-down brackets, the slats may be opened or closed. Disconnect the rail from the brackets to raise and lower the blind.



BOTTOM RAIL



HOLD-DOWN BRACKET

PROTECT YOUR CHILDREN

Be aware that it is possible for children to strangle in window covering cords. To reduce the possibility of such an accident, all cords must be kept out of the reach of children, including infants. Cord cleats are an effective way to implement this essential precaution.

Attach the cord cleats 153mm to 305mm apart at a height where they will be out of the reach of children. Take into account that a child may stand on a baby cot or other furniture in an attempt to reach the cords. Once the cleats are attached, simply wrap the excess cord around them after each use of the shade, as shown. It's fast, easy and safe.



OPERATION

CORD TILT: Pulling on one of the single cords will tilt the slats in one direction, and pulling the other cord will tilt the slats in the opposite direction.

RAISING & LOWERING OF BLIND: to raise, tilt the slats to the fully opened position. Remove the bottom rail from the hold-down brackets (if fitted). Pull the lift cord towards the centre and raise the blind. To lock in position simply move the cord towards the outer edge of the blind to engage the cord lock. To lower, simply pull the cord towards the centre of the blind and lower gently.

CARE AND CLEANING

1. Dust can be easily brushed off at regular intervals using a clean soft cloth, a feather duster, or a vacuum cleaner with brush attachment.
2. To dust, tilt the slats up and then down (but not entirely closed) to reach the entire top and bottom surfaces.
3. To vacuum, use the brush attachment and tilt slats as per 2. above.
4. Slats may be wiped over with warm water and a mild detergent